



www.i-keytec.com

Fusion Intelpage IP



Key Features:

- Dispatches messages to standard POCSAG pagers
- Sturdy rack mount design
- IP/Ethernet connectivity
- HTML browser configuration
- Fully synthesised frequency range
- Available in VHF or UHF bands
- 1W - 100W versions available

Specifications:

Power Supply	110-240VAC 50/60Hz
Frequency Range	VHF 148-174 MHz or UHF 433-470 MHz
External Connectors	Ethernet, 10Mbps, RJ45F Serial RS232C, 300-57600 baud, RJ45F
Pager Database	1,000 pager IDs
Input Protocols	TAP, Comp1/2, Scope, TNPP, Terminal, Tekk
Output Protocols	POCSAG 512, 1200 or 2400bps
Channel Spacing	12.5 kHz (Narrow Band) or 25 kHz (Wide Band)
Duty Cycle	50%
Dimensions	5W – 1RU 19" rack 439 x 205 x 44 mm (17.3 x 8.1 x 1.7") 25/50/100W – 2RU 19" rack 439 x 430 x 88 mm (19 x 16.5 x 3.4")
Weight	5W rack – 2.7 kg (5.9 lb) 25/50/100W rack – 9.5 kg (21.0 lb)
Approvals	FCC, CE, RCM, ROHS, IC, EN60950, IDA, CB

*Specifications subject to change without notice